

* PRODUCT INFORMATION *

HUSKEY™ BIOBASE EP LUBE

DESCRIPTION

HUSKEY BIOBASE EP LUBE is a blend of the finest quality USA grown, biodegradable vegetable oils available then treated with the most effective anti-oxidants, extreme pressure, anti-wear and anti-corrosion additives. PTFE has been added to further enhance load capacity, and reduce friction and wear. **HUSKEY BIOBASE EP LUBE** is readily biodegradable and contains no ozone depleting chemicals, SARA Title 313 chemicals, heavy metals, greenhouse gases, chlorine, phenols, VOC's or Prop. 65 Chemicals. **HUSKEY BIOBASE EP LUBE** is also NSF/U.S.D.A. H-1 *Registered and KOSHER approved, which gives it full acceptability for use in ALL areas where incidental food or potable water contact may occur. **HUSKEY BIOBASE EP LUBE is the ultimate "Green" Lubricant.**

USAGE

HUSKEY BIOBASE EP LUBE is truly multi-service lubricant for extended service under extremely high and low temperature conditions from -20°F to 520°F. **HUSKEY BIOBASE EP LUBE** has proven to be a problem solving lubricant in a wide variety of industries and applications. Some applications include fans, bearings, chains, pumps, conveyors, electrical motors, nuts and bolts, cables, air tools, locks, hinges, guns, etc.

ADVANTAGES

- LUBRICATES, PENETRATES AND PROTECTS
- WIDE TEMPERATURE RANGE
- BIODEGRADABLE AND RENEWABLE RESOURCE BASED
- PROTECTS AGAINST RUST, CORROSION, AND WEAR
- FORMULATED WITH PTFE
- DISPLACES MOISTURE
- NSF H-1 *REGISTERED
- KOSHER APPROVED



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE

* PRODUCT INFORMATION *

TYPICAL PROPERTIES

DESCRIPTION	HUSKEY Product:	BIOBASE EP LUBRICANT
	Color:	Amber
	Base:	Vegetable Oil
	Solid Lubricant:	PTFE
	NSF/U.S.D.A. Rating:	* H-1

<u>Test</u>	<u>ASTM Method</u>	<u>Typical Results</u>
Base Oil Viscosity, cSt @ 40°C	D-445	35.8
cSt @ 100°C	D-445	8.6
Viscosity Index	D-2270	203
Flash Point, °F	D-92	520
Pour Point, °F	D-97	-20
4-Ball Wear Scar (75 °C, 40 Kg, 1 hr.@ 1200 rpm)	D-4172	0.4
Falex Pin and "V" Block, Pass Lbs.	D-3233A	3500

PACKAGE AVAILABILITY

Convenient 1 gal. Jugs (4 ea. Jugs per case)
5 gal. Pail, 15 gal. Keg, and 55 gal. Drum

* NSF H-1 Registration No. 142967

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

06/10



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE