

* PRODUCT INFORMATION *

HUSKEY™ COOLUBE 65 GREASE

DESCRIPTION

HUSKEY COOLUBE 65 is a high performance, low temperature grease designed for high speeds and moderate loads. **HUSKEY COOLUBE 65** is blended from the highest quality petroleum base stocks and selectively treated with rust, oxidation and anti-wear additives coupled with an extremely shear stable thickener system.

USAGE

HUSKEY COOLUBE 65 was designed to provide excellent lubrication, wet or dry, over a wide temperature range (-65°F to 250°F.) in a large variety of industries, including textile, food processing, agriculture, automotive, etc. **HUSKEY COOLUBE 65** meets the performance requirements of MIL-G-10924C and MIL-G-10924D. **COOLUBE 65** is recommended for all bearing surfaces including fan bearings, spindles, freezer bearings, electric tools, slides, conveyors, etc.

ADVANTAGES

- Wide Temperature Range
- Excellent for High Speeds
- Extremely Resistant to Water
- Meets the Requirements of Mil -PRF-10924 C&D and Ford WSB-M1C163-D
- Prevents Rust and Corrosion
- Extreme Pressure Resistant
- Reduces Friction and Wear

TYPICAL PROPERTIES

<u>TEST</u>	<u>ASTM TEST METHOD</u>	<u>RESULTS</u>
Color	-----	Amber
Thickener	-----	Calcium 12 Hydroxy
N.L.G.I. Grade	-----	2
Worked Penetration, 60 Strokes	D-217	265-295
Base Oil Viscosity SUS @ 100°F	D-445	83
SUS @ 210°F		37
cSt @ 40°C		15.1
cSt @ 100°C		3.2
Pour Point, °F	D-97	-65
Flash Point, °F	D-92	300
Dropping Point, °F	D-566	300
Oxidation Stability, (100 hrs. @ 210°F) psi Loss	D-942	5
Oil Separation, % Loss	D-1742	5
Rust Test	D-1743	Pass
Timken OK Load, lbs.	D-2509	45

PACKAGE AVAILABILITY

Convenient 1 gal. pail, 5 gal. Pail, 15 gal. Keg and 55 gal. Drum

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

01/09



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE