

# \* PRODUCT INFORMATION \*

## **HUSKEY™ HTL-500 GREASE**

### **DESCRIPTION**

**HUSKEY HTL-500 GREASE** represents some of the most advanced lubricant technology. It is a versatile, premium quality, synthetic grease fortified with PTFE. Blended completely with pure synthetic base oils, additives and shear stable thickeners to provide maximum equipment protection in extremely high and low temperatures (Operating Range -75° to over 500°F). **HUSKEY HTL-500 GREASE** is also NSF/ U.S.D.A. H-1 \*Registered and KOSHER approved, which gives it full acceptability for use in all areas where incidental food contact may occur.

### **USAGE**

**HUSKEY HTL-500 GREASE** is truly a multi-service lubricant for extended service under extreme high and low conditions. **HUSKEY HTL-500 GREASE** has proven to be a problem solving product in a wide variety of industries and applications. Some such applications include: Freezer bearings, oven bearings and chains, pumps, kilns, conveyors, etc.

### **ADVANTAGES**

- NSF/ U.S.D.A. H-1 \*REGISTERED
- WATER AND STEAM RESISTANT
- NON-MELTING
- KOSHER APPROVED
- NON-STAINING
- WIDE TEMPERATURE RANGE
- REDUCES FRICTION AND WEAR
- FORTIFIED WITH PTFE

\*NSF H-1 Registration No. 059312



### **PACKAGE AVAILABILITY**

Convenient disposable Gun Loader  
13 oz. Cartridges,  
1 gal. pails, 5 gal. Pails, 15 gal. Kegs, and 55 gal. Drums



## **HUSKEY Specialty Lubricants**

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

### **Western Region Office:**

1580 Industrial Avenue, Norco, California 92860  
(951) 340-4000 • Fax: (951) 340-4011  
(888) 4-HUSKEY • [www.huskey.com](http://www.huskey.com)

### **Eastern Region Office:**

8300 Corporate Park Drive, Macedonia, Ohio 44056  
(330) 425-2567 • Fax: (330) 425-9637  
(800) 238-LUBE

# \* PRODUCT INFORMATION \*

## TYPICAL PROPERTIES

### DESCRIPTION

<b>HUSKEY</b> Product:	HTL-500 Grease
Color:	Translucent White
Base Oil:	Synthetic
Thickener:	Synthetic
Texture:	Buttery
Base Solid Lubricant:	Sub-Micron Size PTFE
NSF/U.S.D.A. Rating:	H-1

### TESTS

### ASTM TEST METHOD

### RESULTS

N.L.G.I. Grade	-----	2
Worked Penetration	D-217	
60 Strokes		265
10,000 Strokes		295
Base Oil Viscosity,		
SUS @ 100°F	D-445	240
SUS @ 210°F		53
cSt @ 40°C		47
cSt @ 100°C		7.9
Pour Point, °F	D-97	-75
Flash Point, °F	D-92	510
Dropping Point °F	D-566	None
Oil Separation, % Loss	D-1742	0.0
Corrosion Preventative Test	D-1743	PASS
Four Ball Wear Scar, mm		
(40 Kg. 1 hr. @ 1200 rpm, 75°C)	D-2266	0.45
Four Ball E.P. Wear	D-2596	
Load Wear Index, Kg		30.6
Weld Point, Kg		160

The name of this product or group of products is for product identification purpose only. HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation makes no warranties, representations or conditions of any kind express or implied, whether for merchantability or fitness for use with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation sales personnel are not authorized to amend this warranty limitation. 02/07



## **HUSKEY Specialty Lubricants**

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

### Western Region Office:

1580 Industrial Avenue, Norco, California 92860  
(951) 340-4000 • Fax: (951) 340-4011  
(888) 4-HUSKEY • www.huskey.com

### Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056  
(330) 425-2567 • Fax: (330) 425-9637  
(800) 238-LUBE